CENS ProFlex DX1

Info Sheet



Custom-Made, Modular Digital Noise Protection, with a single digitally optimised mode & 3 stage digital volume control. The DX1 is supplied with WaterShield hydrophobic protection as well as an extended 2 year warranty and as with all CENS digital devices they are tested and certified to EN352-2: 2002 & EN352-7: 2002.

SNR: 25





Technical Info

- Digital DSP circuitry
- Size 13 battery
- Patented modular design
- Multi-softness earpiece

Single General Mode

Optimised for good all-round use with both rifles and shotguns in all shooting disciplines. With its fine tuned general shooting mode, it boosts quieter sounds such as approaching birds and quarry to clear audible levels, giving you the edge on the competition.

6 Module Colours



Digital Volume Control



Digital volume control push button for changing volume level with a short press.

Dedicated Power Button



Dedicated digital power button makes switching on and off easier than ever

Deluxe Packaging






CENS ProFlex DX1



DX1 Output Levels







Attenuation Data Electronic Modules

H=28			M=21			L=19		
Assumed Protection	18.0	18.7	18.7	17.6	20.8	28.6	37.5	38.4
Standard Deviation	8.1	7.2	7.3	8.9	6.8	4.7	3.8	5.2
Mean Attenuation	26.1	25.9	26.0	26.5	27.6	33.3	41.3	43.6
Frequency (Hz)	63	125	250	500	1000	2000	4000	8000

Criterion Levels

Mode No	Н	M	L
1	111	105	105

C€EN352

Hearing Protection. Category III PPE EU2016/435 Type Approval and conformity surveillance (Module D) by: SATRA Technology Europe Limited, Bracetown Business Park, Clonee. D15 YN2P. Ireland. Notified Body 2777.

