CENS ProFlex DX3

Info Sheet



Custom-Made, Modular Digital Noise Protection, with 3 digitally optimised modes & 10 stage digital volume control. The DX3 is supplied with WaterShield hydrophobic protection as well as an extended 2 year warranty and as with all CENS digital devices they are tested and certified to EN352-2: 2002 & EN352-7: 2002.

SNR: 25



Technical Info

- Digital DSP circuitry
- Size 13 battery
- Patented modular design
- Multi-softness earpiece

Modes

Clay Optimised for clay shooting.

Game Optimised for game shooting.

Tactical Optimised for tactical & practical

style shooting.

Deluxe Packaging



6 Metalic Colours



Vocal Feedback



Verbally announces the current mode as you change through them.

User Settings Auto-Save



Remembers the selected mode and volume levels even when switched off.

Digital Multi-Switch



For changing modes, with a long press and volume level with a short press.

Power/Mute Button




Combined power and mute button, for moments when concentration is key.

CENS ProFlex DX3



DX3 Output Levels







Attenuation Data Electronic Modules

SNR=25								
H=28			M=21			L=19		
Assumed Protection	18.0	18.7	18.7	17.6	20.8	28.6	37.5	38.4
Standard Deviation	8.1	7.2	7.3	8.9	6.8	4.7	3.8	5.2
Mean Attenuation	26.1	25.9	26.0	26.5	27.6	33.3	41.3	43.6
Frequency (Hz)	63	125	250	500	1000	2000	4000	8000

Criterion Levels

Mode No	Н	М	L
1	111	105	105
2	112	106	105
3	111	106	104

C€EN352

Hearing Protection. Category III PPE EU2016/435 Type Approval and conformity surveillance (Module D) by: SATRA Technology Europe Limited, Bracetown Business Park, Clonee. D15 YN2P. Ireland. Notified Body 2777.

